



AUSTRALIAN COMMUNICATIONS INDUSTRY FORUM
INDUSTRY SPECIFICATION

**PART F SIGNALLING SYSTEM No. 7 –
APPLICATION OF THE MESSAGE TRANSFER
PART FOR NATIONAL INTERCONNECT**

ACIF G500:2000 PART F

Industry Specification

This Specification is issued in draft form for comment as DR2 ACIF G500.

First published as ACIF G500:1998.

ISBN 1 74000 068 4

© Copyright Australian Communications Industry Forum
PO Box 444, Milsons Point NSW 1565

Disclaimers

1. Notwithstanding anything contained in this Specification:
 - (a) ACIF disclaims responsibility (including where ACIF or any of its officers, employees, agents or contractors has been negligent) for any direct or indirect loss, damage, claim, or liability any person may incur as a result of any:
 - (i) reliance on or compliance with this Specification;
 - (ii) inaccuracy or inappropriateness of this Specification; or
 - (iii) inconsistency of this Specification with any law; and
 - (b) ACIF disclaims responsibility (including where ACIF or any of its officers, employees, agents or contractors has been negligent) for ensuring compliance by any person with this Specification.
2. The above disclaimers will not apply to the extent they are inconsistent with any relevant legislation.

Copyright

This document is copyright. You may reproduce it only as necessary for the purposes of you or your organisation considering or pursuing compliance with this Specification. You must not alter or amend this Specification.

Part F

SIGNALLING SYSTEM No. 7 – APPLICATION OF THE MESSAGE TRANSFER PART FOR NATIONAL INTERCONNECT

0. General

This document forms part of the Australian Communications Industry Forum (ACIF) G.500 signalling protocol specification for interconnection services to be used in the Australian domestic network.

This document is based on ITU-T recommendations Q.701 to Q.709 (1988) which remains copyright of the ITU-T. This document describes the modifications required to ITU-T recommendations Q.701 to Q.709 to suit Australian network requirements.

0.1 Participants

The ACIF group (Network Reference Panel: Working Committee #7 “Signalling and Interconnect Dial Plan”) that developed this document consisted of the following companies and representatives:

<u>Representative</u>	<u>Company / Organisation</u>	
<u>Gary McLaren</u>	<u>Siemens</u>	<u>Chairperson</u>
<u>Alan Arthurell</u>	<u>Alcatel</u>	<u>Secretary</u>
<u>Sam Fois</u>	<u>Telstra</u>	<u>Interconnection Implementation Plan Editor</u>
<u>Roger Nicoll</u>	<u>Primus</u>	<u>Interconnection Implementation Plan Editor</u>
<u>Catherine Tritt</u>	<u>Telstra</u>	<u>Signalling Specification Editor</u>
<u>Adrian Jang</u>	<u>Telstra</u>	<u>Signalling Specification Editor</u>
<u>Sarath Weerasinghe</u>	<u>Nortel</u>	<u>Signalling Specification Editor</u>
<u>Wayne Thomas</u>	<u>AAPT</u>	
<u>Peter Ramsey</u>	<u>ACA</u>	
<u>Mankin Leung</u>	<u>Alcatel</u>	
<u>Ian Bentley</u>	<u>C&W Optus</u>	
<u>Kamal Wanigatunga</u>	<u>C&W Optus</u>	
<u>Terry Gillespie</u>	<u>C&W Optus</u>	
<u>James Dam</u>	<u>C&W Optus</u>	
<u>Mark Hollis</u>	<u>Ericsson</u>	
<u>Nebojsa Dikic</u>	<u>Ericsson</u>	
<u>Craig Hennessy</u>	<u>Global One</u>	
<u>Elizar Franco</u>	<u>Global One</u>	
<u>Mark Ristich</u>	<u>Lucent</u>	
<u>Michelle Fong</u>	<u>Lucent</u>	
<u>Paul Coleman</u>	<u>MCI/Worldcom</u>	
<u>Thomas Kam</u>	<u>Nortel</u>	
<u>Peter Hull</u>	<u>Nortel</u>	
<u>Trinh Lam</u>	<u>Primus</u>	
<u>Adrian Pizzica</u>	<u>Telstra</u>	
<u>Phil Walls</u>	<u>Telstra</u>	
<u>Dusica Vukadinovic</u>	<u>Vodafone Network</u>	
<u>Matthew Ah Yong</u>	<u>Vodafone Network</u>	
<u>Davorka Karacic</u>	<u>Vodafone Network</u>	

1. Introduction

This document describes the national interconnect implementation of the Message Transfer Part (MTP) of Signalling System No.7 recommended for use by the ACIF.

The MTP implementation described by this document is recommended for use between interconnecting national switch operators. The choice and implementation of the User Parts is beyond the scope of this document.

Any clauses of CCITT Recommendations Q.701 to Q.709, 1988, which are not mentioned in this document are deemed to be fully applicable for national interconnect. These clauses do not require any clarification.

2. References

ITU-T Recommendations Q.701 to Q.709 (1988).

3. Requirements

3.1 Changes to ITU-T Recommendation Q.701 - Functional Description of the Message Transfer Part (MTP) of Signalling System No. 7

Section 2.2.2 Only 64 kbit/s signalling data links will be used.

Section 5 The MTP is required to carry MSUs of up to 272 octets in length

Section 7.2.6 The MTP will support MSUs up to 272 octets. Analysis of the LSSU D-bit is not required on signalling links.

3.2. Changes to ITU-T Recommendation Q.702 - Signalling Data Link

1.3 The 64 kbit/s signalling data link will be delivered as a channel in a 2048 kbit/s digital multiplex signal as defined in Recommendation G.704.

1.4 Analogue signalling data links will not be used.

1.8 Multiplex structures or switchable functions used to connect the signalling data link within an exchange are implementation dependent.

2.1.2,2.1.3,2.2.1,2.2.2,2.2.3 Only 64 kbit/s signalling data links will be used.

5.1 Signalling data links will reside in time slot 1.

5.2 8448 kbit/s digital paths will not be used.

5.3 1544 kbit/s digital paths will not be used.

5.5 Signalling data links established over data circuits will not be used.

6 Analogue signalling data links will not be used.

3.3. Changes to ITU-T Recommendation Q.703 - Signalling Link

1.4.1 Only the basic method of error correction will be used.

1.4.3 The preventive cyclic retransmission method will not be used.

6 The preventive cyclic retransmission method will not be used.

3.4. Changes to ITU-T Recommendation Q.704 - Signalling Network Functions and Messages

1.4.1 Only basic method error correction will be used.

2.2.3 The standard label structure of length 32 bits will be used. The signalling point code value of zero is reserved and will not be allocated.

2.3.5 Multiple congestion levels will not be used.

2.3.5.2 Multiple congestion levels will not be used.

3.3.5.2 Signalling route restricted will not be used.

3.8.2,3.8.3,3.8.4 Just one level of congestion onset and abatement will be used. Multiple levels of congestion are not used.

3.8.5.2 The signalling routeset congestion test is not used.

4.7 Signalling route restriction is not used.

6.2.3 iii) The transfer restricted procedure is not used.

11.2.4,11.2.5 Multiple congestion levels are not used.

12.6 Automatic allocation of signalling data links will not be used.

13.4 Transfer Restricted is not used.

13.7 Multiple congestion levels are not used.

13.8 Multiple congestion levels are not used.

13.9 The signalling routeset congestion test is not used.

14.2.1 The same User Part service indicators will apply to the national network as used in the international network.

14.2.2 All messages sent on the MTP must use a network indicator of “national network”.

15.9 Transfer Restricted message is not used.

15.13 Signalling Data Link Connection Order message is not used.

15.14 Signalling Data Link Connection Acknowledgement message is not used.

15.16 Signalling Routeset Congestion Test message is not used.

3.5. Changes to ITU-T Recommendation Q.705 - Signalling Network Structure

7. Signalling network structure is a matter for bilateral discussion. Specifically the use of STPs, multiple links in a linkset, load-sharing across linksets, and the use of priority-ordered linksets is a matter for bilateral agreement.

3.6. Changes to ITU-T Recommendation Q.706 - Message Transfer Part Signalling Performance

No variations.

3.7. Changes to ITU-T Recommendation Q.707 - Testing and Maintenance

No variations.

3.8. Changes to ITU-T Recommendation Q.708 - Numbering of International Point Codes

1. International Signalling Point Codes are not recommended for national interconnect. National signalling point codes will be used.

2. National signalling point codes are allocated as decimal numbers from the range 1 - 16,383. Signalling Point Code 0 is reserved. Point code allocations are currently administered by Telstra.

3.9. Changes to ITU-T Recommendation Q.709 - Hypothetical Signalling Reference Connection

No variations.

The Australian Communications Industry Forum Ltd (ACIF) is a communications self-regulatory body established in 1997 by the industry to manage communications self-regulation within Australia.

The primary role of ACIF is to develop and administer Technical Standards, Industry Codes and industry support services that promote both the long-term interest of end-users and the efficiency and international competitiveness of the Australian communications industry.

ACIF is an industry initiative, funded and resourced by the industry, with a membership that encompasses all industry sectors. ACIF comprises a Board, Advisory Assembly, Executive, six standing Reference Panels and a number of task-specific Working Committees.

Technical Standards and Industry Codes are prepared by Working Committees made up of experts from industry, consumer, government, and other bodies. The requirements or recommendations contained in ACIF's published documents are a consensus of views of representative interests and also take into account comments received from other sources.

Care should be taken to ensure that material used is from the current version of the Standard or Code and that it is updated whenever the Standard or Code and is amended or revised. The number and date of the Standard or Code should therefore be clearly identified. If in doubt please contact ACIF.



Published by:

**THE AUSTRALIAN COMMUNICATIONS
INDUSTRY FORUM LTD**

Level 9, 32 Walker Street
North Sydney NSW 2060

Correspondence: PO Box 444
Milsons Point NSW 1565

Telephone: (02) 9959 9111
Facsimile: (02) 9954 6136

E-mail: acif@acif.org.au

Web Site: <http://www.acif.org.au/>